

Delo® Protection for Agricultural Equipment



Engine Crankcase

- Delo 400 LE Synthetic SAE 5W-40
- Delo 400 LE SAE 15W-40
- Delo 400 XLE Synblend SAE 10W-30
- Delo 400 XLE Synblend SAE 15W-40
- Delo 400 SD Severe Duty SAE 15W-30*



Coolant System

- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant



Bearings

- Delo Grease ESI
- Delo Heavy Duty EP
- Delo Grease EP



Hydraulic System

- Chevron 1000 THF
(For units with common THF reservoirs)
- Chevron Synthetic All Weather THF
(For units with common THF reservoirs)
- Rando HDZ
- Rando HD



Differentials & Gear Drives

- Chevron 1000 THF
(For units with common THF reservoirs)
- Chevron Synthetic All Weather THF
(For units with common THF reservoirs)
- Delo TorqForce SAE 50 (CAT TO-4)
- Delo Gear ESI® SAE 80W-90 (API GL-5/MT-1)

Transmissions (Manual & Automatic)

- Chevron 1000 THF (For units with common THF reservoirs)
- Chevron Synthetic All Weather THF (For units with common THF reservoirs)
- Delo TorqForce MP (For TO-4 or Allison C4 Fluid Requirements)
- Delo TorqForce SAE 30 (For TO-4 or Allison C4 Fluid Requirements)

*Severe duty applications typically have lower drain intervals relative to other duty cycles. See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in tractors. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.



Delo®
Let's go further.™

A Chevron company product

© 2016 Chevron Canada Limited. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC. CH2016DBTBAE