

Delo® Protection for Construction Equipment



Hydraulic System

Delo TorqForce SAE 10W (CAT TO-4)
Delo TorqForce Syn SAE 5W-20
Rando® HDZ
Ursa® Hydraulic SAE 10W



Bearings & Grease Points

Delo Heavy Duty EP
Delo Heavy Duty Moly 5% EP
Delo Heavy Duty Synthetic Moly 5% EP

Transmissions

Delo TorqForce SAE 30 (CAT TO-4)
Delo TorqForce MP (CAT TO-4M)
Ursa Hydraulic SAE 10W (Hydrostatic)



Engine Crankcase

Delo 400 LE SAE 15W-40
Delo 400 XLE Synblend SAE 10W-30
Delo 400 XLE Synblend SAE 15W-40
Delo 400 SD Severe Duty SAE 15W-30*



Coolant System

Delo ELC Antifreeze/Coolant – Premixed 50/50
Delo XLC Antifreeze/Coolant – Premixed 50/50



Differentials & Gear Drives

Delo Syn-Gear XDM SAE 75W-90
Delo Gear ESI® SAE 80W-90
Delo TorqForce SAE 50 (CAT TO-4)

*Severe duty applications typically have lower drain intervals relative to other duty cycles.
See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in construction. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.



Delo®

Let's go further.™

A Chevron company product

© 2016 Chevron Canada Limited. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC.
CH2016DBTBCE