

Delo® Bumper-to-Bumper Protection for Wheel Loaders



Transmissions

- Delo TorqForce SAE 30
- Delo TorqForce MP
- Delo TorqForce Syn SAE 5W-20



Engine Crankcase

- Delo 400 LE Synthetic SAE 5W-30, 5W-40
- Delo 400 LE SAE 15W-40
- Delo 400 XLE Synblend SAE 10W-30
- Delo 400 XLE Synblend SAE 15W-40
- Delo 400 SD Severe Duty SAE 15W-30*



Coolant System

- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant

Gear Drive

- Delo TorqForce SAE 50
- Delo TorqForce FD SAE 60

Hydraulic System

- Delo TorqForce SAE 10W
- Delo TorqForce MP
- Delo TorqForce Syn SAE 5W-20
- Clarity® Synthetic Hydraulic AW
- Rando® HDZ



Bearings & Grease Points

- Delo Heavy Duty Moly 5% EP
- Delo Heavy Duty Moly 3% EP
- Delo Heavy Duty Synthetic Moly 5% EP



*Severe duty applications typically have lower drain intervals relative to other duty cycles. See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in wheel loaders. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.



Delo®
Let's go further.™