




# Delo® Protection for Light Duty Diesel Trucks

## Engine Crankcase

- Delo 400 LE Synthetic SAE 5W-30
- Delo 400 LE Synthetic SAE 5W-40
- Delo 400 LE SAE 15W-40
- Delo 400 XLE Synblend SAE 10W-30
- Delo 400 XLE Synblend SAE 15W-40
- Delo 400 SD Severe Duty SAE 15W-30\*



## Differentials & Axles

- Delo Syn-Gear XDM SAE 75W-90
- Delo Gear ESI® SAE 80W-90



## Transmissions (Automatic)

- Delo Syn ATF HD
- Chevron ATF HD 389
- Havoline® Full Synthetic Multi-Vehicle ATF
- Havoline Multi-Vehicle ATF



## Grease Points, Rods, Pins & Bearings

- Delo Grease ESI®
- Delo Grease EP



## Coolant System

- Delo ELC Antifreeze/Coolant
- Delo XLC Antifreeze/Coolant
- Havoline® Extended Life Antifreeze/Coolant DEX-COOL®
- Havoline Universal Antifreeze/Coolant



## Power Steering

- Havoline Power Steering Fluid

\*Severe duty applications typically have lower drain intervals relative to other duty cycles. See OEM recommendations for drain interval recommendations.

The product recommendations provide general guidelines for use in light duty diesel trucks. All manufacturers have different coolant and lubricant requirements and recommendations. It will be important to contact a Chevron representative or refer to the Original Equipment Manufacturer manual to confirm the proper product is used for the application. You may contact our LUBETEK organization (800-LUBE-TEK) for confirmation of specific OEM specifications.

DEX-COOL® is a registered trademark of General Motors Corporation.



**Delo®**  
Let's go further.™

A Chevron company product

© 2016 Chevron Canada Limited. All rights reserved. All trademarks are the property of Chevron Intellectual Property LLC. CH2016DBTBLDE